


Specification Sheet

Part Number: MB310M4



Screw-Mount Base, .75" x .75", .14" Max Tie Width, .12" Hole Dia, PA66, White, 1000/pkg

| | |
|--------------------------------|--|
| Article Number | 151-28305 |
| Type | MB3 |
| Color | White (WH) |
| Features & Benefits | <ul style="list-style-type: none">•Compact size fits most mounting applications.•Simple to install with a screw or rivet.•Single hole attachment with two-way entry for cable tie. |
| Quantity Per | bag |
| Product Description | These cable tie mounts are compact in size. They are designed for simple yet robust installation. They pair with a cable tie for mounting applications including telecom equipment, switchgear and control cabinets. |
| Short Description | Screw-Mount Base, .75" x .75", .14" Max Tie Width, .12" Hole Dia, PA66, White, 1000/pkg |

Global Part Name

MB3-PA66-WH

Length L (Imperial)

0.75

Length L (Metric)

19.0

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

0.75

Width W (Metric)

19.0

Cable Ties

T18 - T30

Height H (Imperial)

.15

Height H (Metric)

3.80

Cable Tie Width Max (Imperial)

0.14

Cable Tie Width Max (Metric)

3.6

Mounting Hole Diameter D (Imperial)

0.12

Mounting Hole Diameter D (Metric)

3.0 mm

Mounting Hole Diameter D Max (Metric)

3.0

Mounting Hole Centers (Imperial)

0.52

| | |
|--|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity(Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909987 |