

Termination resistor - FL LCX 50-OHM-RSMA - 2702702


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The termination resistor is screwed onto an unused antenna connection of a WLAN device, e.g., in leaky wave applications. This terminates the connection with the correct impedance and prevents undesirable emission.



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 299211
GTIN	4055626299211

Technical data

Dimensions

Length	17.4 mm
Diameter	8 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

General

Frequency range	0 GHz ... 6 GHz
Impedance	50 Ω
Connection method	RSMA (male)

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>