	E G			0	B		
4	Z Pread A L L L L L L L L L L L L L	ØF					4
ω				LAYOUT SHOWN AS EXAN	1PLE		3
		Keying Shown as example					
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
	-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	F22.25 MaxZ31.5 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of the (professional recommendation,	does not comply with Parties or by a third party		
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed		2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D113W0	)8SA		
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 27-09-2	2016 First Release			
_			ISS DAT Designed By:	E Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
			TITLE	Aluminium Ir	nline plug 8D series		
<b>_</b>	BASIC SERIES:8D1-13WSHELL TYPE : In line Receptacle </td <td>08 S A</td> <td>SCALE</td> <td>General linear Tolerances:</td> <td>NPRDS / PROJECT <b>859</b></td> <td></td> <td>1</td>	08 S A	SCALE	General linear Tolerances:	NPRDS / PROJECT <b>859</b>		1
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIE CONTACT TYPE : SOCKET(5		SOURIAU WWW.SOURIAU.COM This document is the properative SOURIAU it must not be reproduce communicated without period			
	PLATING : W = Olive drab Cadmium	CONTACT LAY		SOURIAU D	RG N°	SHEET 1/2	
L	H G	FE	D	8D113W08	B A	±/ =	

ſ	Т	۵	П	п		0	Φ	A		
		Contact Layout								
4	Corpos	$\begin{array}{c} & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ \hline & & & \\ & & \\ \hline & & & \\ &$								4
	Shell Arrangement Nu size no. c	A         +.065 (1.65)         +.157 (3.99)           B         +.170 (4.32)         +.000 (0.00)           C         +.120 (3.05)        120 (3.05)           D         .000 (0.00)        170 (4.32)           E        120 (3.05)        120 (3.05)           F        170 (4.32)         +.000 (0.00)           G        065 (1.65)         +.157 (3.99)           H         +.000 (0.00)         +.044 (1.12)							-	_
ω	L									3
						SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
N								n & Control List t Listed		2
						PN: 8D113W08SA				
					A 27-09-201	16 First Release				
					ISS DATE Designed By:	Latest modification - by Date:	CL	STOMER DRAWING	10D N°	_
					TITLE	Alun	ninium Inline plug 8			
<u> </u>					SCALE NA	Genera Tolera ±	ances:	NPRDS / PROJECT <b>859</b>	of	1
		SOURIAU       WWW.SOURIAU.COM       This document is the property of SOURIAU         it must not be reproduced or communicated without permission       it must not be reproduced or communicated without permission								
					FORMAT A3		RIAU DRG N° 13W08SA-C		SHEET 2/2	
l	Н	G	F	E	D	C	<u>B</u>	A	,-	