REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2014-02-13	Fisher	Initial Release

ALTW
DCC. DEPT.
CONFIDENTIAL
2014.02.19
ISSUED







ALTW
CONFIDENTIAL
2014-02-13
R&D DEPT.

SSLII-P4LP0-B22AXX

- 01: L=100±20 mm.
  02: L=200±20 mm.
  04: L=400±25 mm.
  Standard Length is 400mm
  Wire Length Range(L): 100~9900mm
- 22: 22AWG
- LOCK&LATCH OPTION
  B: WITH W2B LOCK

Conn. 1	Wire Color
4	Yellow 黃
3	Orange 橙
2	Red 紅
1	Brown 棕
Pin Out	

Notes:
* QC Important Dimensions To Check.
* Housing: Thermoplastic, UL94V-0, Natural White.
* Terminal: Copper Alloy, Gold Plated.
* Hood: Thermoplastic, UL94V-0, Natural White.
* SR Mold: PP, UL94V-0, Natural White.
* W2B Lock: Thermoplastic, UL94V-0, Natural White.
* Wire: UL1430 22AWG,
  Brown/Red/Orange/Yellow
* Wire Length Tolerance: ±5%mm.

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: SSLI.1 WIRE ASS'Y, WITH W2B LOCK 4-POS, PLUG TO OPEN

SCALE 3:1 | SIZE A4 | SHEET 1 OF 1
REV. A | WC-REV. A.1 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO		DRAWN BY	Fisher_Wang	DATE	2014-02-13
DWG NO	SSLII-P4LP0-B22AXX	CHECKED BY	Ivan_Lin	DATE	2014-02-13
CUSTOMER	ALTW	APPROVED BY	Kevin_Hu	DATE	2014-02-13

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.