


Material: UL94 V-2 Nylon 6/6  
Color: Natural

Part No.	A	
	mm	in
CBLSP305A	2.5	.098
CBLSP310A	3	.118
CBLSP315A	3.5	.138
CBLSP320A	4	.157
CBLSP325A	4.5	.177
CBLSP330A	5	.197
CBLSP335A	5.5	.217
CBLSP340A	6	.236
CBLSP345A	6.4	.252
CBLSP350A	7	.276
CBLSP355A	8	.315
CBLSP360A	9	.354
CBLSP365A	10	.394
CBLSP370A	11	.433
CBLSP375A	12	.472
CBLSP380A	15	.591

TO SNAP LOCK IN A 3.5 (.137) Ø HOLE, IN  
A 1.2 - 1.7 (.047 - .067) PANEL THICKNESS



TO SNAP LOCK IN A 3.5 (.137) Ø HOLE, IN  
A 1.2 - 1.7 (.047 - .067) PANEL THICKNESS

TOLERANCES  
UNLESS NOTED  
≤ 5 mm ±0.2  
5 - 20 mm ±0.3  
20 - 40 mm ±0.4  
40 - 60 mm ±0.5  
60 - 100 mm ±0.8  
≥ 100 mm ±1.0

TITLE: DUAL LOCKING CIRCUIT BOARD SUPPORT		DWN: CLC		DWG IN MM (IN)	
FILE: CBLSP3XX	SHEET: 1 OF 1	SHEET SIZE: A	DT: 01/08/15	PART #	PRINT TYPE
RE:			SEE TABLE		CA